



OUR HEATSEEKER NOVAS INVERTER HEAT PUMPS ARE AN ENERGY EFFICIENT AND ENVIRONMENTALLY FRIENDLY WAY TO ENJOY A LONGER SWIM SEASON, HEATING THE POOL BY EXTRACTING HEAT FROM THE OUTSIDE AIR.

Inverter technology allows you to vary or modulate the speed of the compressor – much like a variable-speed swimming pool pump. This enhances the performance of the heat pump and maximises energy efficiency. The Heatseeker NovaS inverter heat pumps provide lower operating costs, delivering outstanding electrical savings and reducing your annual energy consumption by up to 30%.

SMART CLIMATE CONTROL

GREATER FUNCTIONALITY & MORE COMFORT

The Heatseeker NovaSwitch and NovaLink are ancillary products that assist in the primary operation of the heat pump. Heatseeker NovaLink is used for an all in one system for autonomous control of heat pumps in line with the filtration system. Heatseeker NovaSwitch is used for a plug and play automation unit recommended for heat pump systems with independent circulation pumps.





















COMPRESSOR





REFRIGERANT

WI-FI ENABLED

TECHNICAL DATA AND SPECIFICATIONS

| SPECIFICATIONS | | | | | |
|---|-------------|------------------------------------|------------------|------------------|------------------|
| MODEL | | 9 KW | 13 KW | 17 KW | 20 KW |
| Mode Type | | Heat & Cool | | | |
| Discharge | | Side | | | |
| Fan Quantity | | 1 | | | |
| Performance at Air 27°C, Water 26°C, H | umidity 80% | | | | |
| Heat Capacity | kW | 9.5 | 13 | 16.5 | 20 |
| COP | | 6.4-13.5 | 5.8-13.1 | 6.2-13.6 | 6.5-13.8 |
| Performance at Air 15°C, Water 26°C, Ho | umidity 70% | | | | |
| Heat Capacity | kW | 7.1 | 9.2 | 12.6 | 14.5 |
| COP | | 4.7-7.4 | 4.5-7.1 | 4.7-7.4 | 4.8-7.5 |
| General | | | | | |
| Rated input power at air 15°C | kW | 0.20-1.51 | 0.27-2.04 | 0.32-2.68 | 0.35-3.02 |
| Rated input current at air 15°C | Amps | 8.4 | 10.9 | 16.6 | 17.5 |
| Circuit Breaker | Amps | 15 | 15 | 20 | 25 |
| Power Supply | | 240v / 50Hz / 1PH | | | |
| Pool Volume - Cold Climate | Litres | ≤20,000 | ≤30,000 | ≤40,000 | ≤50,000 |
| Pool Volume - Warm Climate | Litres | ≤30,000 | ≤40,000 | ≤50,000 | ≤60,000 |
| Advised Flow Rate | L/min | 53 | 66 | 86 | 100 |
| Inlet / Outlet | mm | 50 | | | |
| Compressor | | Twin-rotary Mitsubishi DC Inverter | | | |
| Heat Exchanger | | Spiral titanium tube in PVC | | | |
| Casing | | Black ABS | | | |
| Noise Level (1m) | dBA | 39-51 | 42-53 | 43-54 | 44-55 |
| Weight / Dimensions | | | | | |
| Net Weight | kg | 45 | 45 | 60 | 70 |
| Net Dimensions L x W x H | mm | 1002 x 403 x 602 | 1002 x 403 x 602 | 1048 x 435 x 767 | 1161 x 470 x 862 |

The sizing of heat pumps are based on pool volume for seasonal swimming with the use of a Heatseeker Pool Cover.









WI-FI ENABLED

CONTROL YOUR HEAT PUMP FROM ANYWHERE, ANYTIME.

Easily monitor, control and manage the operation of your Heatseeker Nova inverter heat pump range from a mobile device using the Handy Heat Pump iOS & Android app.





Available from: